



SOLVAY

Material Safety Data Sheet

Page: 1

RHEOMER 33T

Date Prepared: 10/03/13

Supersedes Date: 9/27/13

1. PRODUCT AND COMPANY IDENTIFICATION

SOLVAY USA, INC.
NOVECARE
CN 7500
8 Cedar Brook Drive
Cranbury, NJ 08512-7500 US

Emergency Phone Numbers:
FOR EMERGENCIES INVOLVING A SPILL, LEAK, FIRE, EXPOSURE OR ACCIDENT
CONTACT: CHEMTREC (800-424-9300 within the United States or
703-527-3887 for international collect calls) or SOLVAY CAERS
(Communication and Emergency Response System) at 800-916-3232.

For Product Information:
800-973-7873

Chemical Name or Synonym:
PROPRIETARY LATEX POLYMER

2. HAZARDS IDENTIFICATION

A. EMERGENCY OVERVIEW:

Physical Appearance and Odor:
milky white / liquid, acrylic odor.

Warning Statements:
CAUTION! MAY CAUSE SKIN AND EYE IRRITATION.

B. POTENTIAL HEALTH EFFECTS:

Acute Eye:
May cause redness, irritation.

Acute Skin:
May cause redness, inflammation, irritation.

Acute Inhalation:
Inhalation not likely. May cause upper respiratory tract irritation.

Acute Ingestion:

May cause nausea, vomiting, irritation.

Chronic Effects:

This product does not contain any ingredient designated by IARC, NTP, ACGIH or OSHA as probable or suspected human carcinogens.

3. COMPOSITION/INFORMATION ON INGREDIENTS

Component	CAS Reg Number	OSHA Hazard	% WT/WT
PROPRIETARY LATEX POLYMER	*****	N	100

4. FIRST AID MEASURES

FIRST AID MEASURES FOR ACCIDENTAL:

Eye Exposure:

Hold eyelids open and flush with a steady, gentle stream of water for at least 15 minutes. Seek medical attention.

Skin Exposure:

In case of contact, immediately wash with plenty of soap and water for at least 5 minutes. Seek medical attention. Remove contaminated clothing and shoes. Clean contaminated clothing and shoes before re-use.

Inhalation:

Inhalation is not an expected route of exposure. If respiratory irritation or distress occurs remove victim to fresh air. Seek medical attention if respiratory irritation or distress continues.

Ingestion:

Do not induce vomiting, unless directed to do so by a physician. If victim is conscious and alert, wash out mouth with water and keep at rest. Do not leave victim unattended. Vomiting may occur spontaneously. To prevent aspiration of swallowed product, lay victim on side. Seek medical attention.

MEDICAL CONDITIONS POSSIBLY AGGRAVATED BY EXPOSURE:

Skin contact may aggravate existing skin disease. Inhalation of product may aggravate existing chronic respiratory problems such as asthma, emphysema or bronchitis.

NOTES TO PHYSICIAN:

All treatments should be based on observed signs and symptoms of distress in the patient. Consideration should be given to the possibility that overexposure to materials other than this product may have occurred.

Treat symptomatically. No specific antidote available.

5. FIRE FIGHTING MEASURES

FIRE HAZARD DATA:

Flash Point:
> 93 C (200 F). Flammability Class: WILL BURN.

Method Used:
Closed cup

Flammability Limits (vol/vol%):	Lower:	Upper:
	No Data	No Data

Extinguishing Media:
Recommended (small fires): dry chemical, carbon dioxide, Recommended (large fire): alcohol foam, universal foam, water spray, Not recommended: water jet (frothing possible).

Special Fire Fighting Procedures:
Firefighters should wear NIOSH/MSHA approved self-contained breathing apparatus and full protective clothing.

Unusual Fire and Explosion Hazards:
Product will burn under fire conditions. When water has evaporated, the residue will burn.

Hazardous Decomposition Materials (Under Fire Conditions):
oxides of carbon

6. ACCIDENTAL RELEASE MEASURES

Evacuation Procedures and Safety:
Wear appropriate protective gear for the situation. See Personal Protection information in Section 8.

Containment of Spill:
Stop leak if it can be done without risk. Dike spill using absorbent or impervious materials such as earth, sand or clay. Follow procedure described below under Cleanup and Disposal of Spill.

Cleanup and Disposal of Spill:
Absorb with an inert absorbent. Sweep up and place in an appropriate closed container (see Section 7: Handling and Storage). DO NOT RETURN MATERIAL TO ITS ORIGINAL CONTAINER. Clean up residual material by washing area with water. Collect washings for disposal. Decontaminate tools and equipment following cleanup.

Environmental and Regulatory Reporting:
Do not flush to drain. Prevent material from entering public sewer system or any waterways. Spills may be reportable to the National Response Center (800-424-8802) and to state and/or local agencies.

7. HANDLING AND STORAGE

Minimum/Maximum Storage Temperatures:
5 to 35 C (41 to 95 F)

Handling:

Do not get in eyes. Avoid direct or prolonged contact with skin. Avoid breathing vapors and mists. DO NOT ALLOW TO FREEZE.

Ethylene oxide may collect in container head space. Although concentrations are expected to remain below established exposure limits, provide adequate ventilation when accessing or working with open containers and tanks.

Storage:

Store in an area that is dry, well-ventilated, Store in tightly closed containers. away from ignition sources, away from incompatible materials (see Section 10. Stability and Reactivity).

8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Introductory Remarks:

These recommendations provide general guidance for handling this product. Because specific work environments and material handling practices vary, safety procedures should be developed for each intended application. While developing safe handling procedures, do not overlook the need to clean equipment and piping systems for maintenance and repairs. Waste resulting from these procedures should be handled in accordance with Section 13: Disposal Considerations.

Assistance with selection, use and maintenance of worker protection equipment is generally available from equipment manufacturers.

Exposure Guidelines:

No exposure limits were found for this product or any of its ingredients.

Engineering Controls:

Where engineering controls are indicated by use conditions or a potential for excessive exposure exists, the following traditional exposure control techniques may be used to effectively minimize employee exposures: general area dilution/exhaust ventilation.

Respiratory Protection:

When respirators are required, select NIOSH/MSHA approved equipment based on actual or potential airborne concentrations and in accordance with the appropriate regulatory standards and/or industrial recommendations.

For reasonably foreseeable industrial end uses of this material, respiratory protection should not be necessary.

Eye/Face Protection:

Eye and face protection requirements will vary dependent upon work

environment conditions and material handling practices. Appropriate ANSI Z87 approved equipment should be selected for the particular use intended for this material.

Eye contact should be prevented through use of chemical safety glasses with side shields or splash proof goggles. An emergency eye wash must be readily accessible to the work area.

Skin Protection:

Skin contact must be prevented through the use of permeation resistant clothing, gloves and footwear, selected with regard for use conditions and exposure potential. An emergency shower must be readily accessible to the work area. Consideration must be given both to durability as well as permeation resistance.

Work Practice Controls:

Personal hygiene is an important work practice exposure control measure and the following general measures should be taken when working with or handling this material:

- (1) Do not store, use, and/or consume foods, beverages, tobacco products, or cosmetics in areas where this material is stored.
- (2) Wash hands and face carefully before eating, drinking, using tobacco, applying cosmetics, or using the toilet.
- (3) Wash exposed skin promptly to remove accidental splashes or contact with this material.

9. PHYSICAL AND CHEMICAL PROPERTIES

Physical and Chemical properties here represent typical properties of this product. Contact the business area using the Product Information phone number in Section 1 for its exact specifications.

Physical Appearance:

milky white / liquid.

Odor:

acrylic odor.

pH:

2.1 to 2.8 at 100 wt/wt%.

Specific Gravity:

>= 1 at 20 C (68 F).

Water Solubility:

dispersible

Melting Point Range:

Not Available

Freezing Point Range:

< 5 C (41 F)

Boiling Point Range:
~ 100 C (212 F) at 760 mmHg

Vapor Pressure:
Not Available

Vapor Density:
Not Available

Evaporation Rate:
< 1 (Butyl Acetate = 1)

Percent Non-Volatiles by Weight:
< 31

Percent Volatiles by Volume:
> 69

Viscosity:
viscosity (centipoises) : < 50 cps at 23 C (73 F).

Octanol/Water Partition Coefficient:
Not Available

10. STABILITY AND REACTIVITY

Chemical Stability:
This material is stable under normal handling and storage conditions described in Section 7.

Conditions To Be Avoided:
heat
open flame
freezing
ignition sources

Materials/Chemicals To Be Avoided:
strong bases
strong acids
strong oxidizing agents
strong reducing agents

The Following Hazardous Decomposition Products Might Be Expected:

Decomposition Type: thermal
oxides of carbon

Hazardous Polymerization Will Not Occur.

Avoid The Following To Inhibit Hazardous Polymerization:
not applicable

11. TOXICOLOGICAL INFORMATION

Acute Eye Irritation:

The following data are for similar or related products.

Toxicological Information and Interpretation

eye - eye irritation, **.

Non-irritating.

Acute Skin Irritation:

The following data is for similar or related products.

Toxicological Information and Interpretation

skin - skin irritation, **.

Non-irritating.

Acute Dermal Toxicity:

No test data found for product.

Acute Respiratory Irritation:

No test data found for product.

Acute Inhalation Toxicity:

No test data found for product.

Acute Oral Toxicity:

No test data found for product.

Chronic Toxicity:

This product does not contain any substances that are considered by OSHA, NTP, IARC or ACGIH to be "probable" or "suspected" human carcinogens.

No additional test data found for product.

12. ECOLOGICAL INFORMATION**Ecotoxicological Information:****Ecotoxicological Information and Interpretation:**

EC50 - effective concentration 50% of test species, > 100 mg/l/48 hr, freshwater invertebrate: Daphnia (water flea).

Chemical Fate Information:

Not readily biodegradable.

13. DISPOSAL CONSIDERATIONS**Waste Disposal Method:**

Chemical additions, processing or otherwise altering this material may make the waste management information presented in this MSDS incomplete, inaccurate or otherwise inappropriate. Please be advised that state and local requirements for waste disposal may be more

restrictive or otherwise different from federal laws and regulations. Consult state and local regulations regarding the proper disposal of this material.

Container Handling and Disposal:

Any containers or equipment used should be decontaminated immediately after use. Consult state and local regulations regarding the proper disposal of container.

EPA Hazardous Waste - NO

14. TRANSPORT INFORMATION

Transportation Status: IMPORTANT! Statements below provide additional data on listed transport classification. The listed Transportation Classification does not address regulatory variations due to changes in package size, mode of shipment or other regulatory descriptors.

US DOT:

Shipping Name: NOT REGULATED

TDG:

Shipping Name: NON DANGEROUS

IMO:

Shipping Name: NOT REGULATED

IATA:

Shipping Name: NOT REGULATED

15. REGULATORY INFORMATION

Inventory Status

Inventory	Status
UNITED STATES (TSCA)	E
CANADA (DSL)	Y
EUROPE (EINECS/ELINCS)	N
AUSTRALIA (AICS)	N
JAPAN (MITI)	N
SOUTH KOREA (KECL)	N

Y = All ingredients are on the inventory.

E = All ingredients are on the inventory or exempt from listing.

P = One or more ingredients fall under the polymer exemption or are on the no longer polymer list. All other ingredients are on the inventory or exempt from listing.

N = Not determined or one or more ingredients are not on the inventory and are not exempt from listing.

FEDERAL REGULATIONS

Inventory Issues:

All functional components are either listed on the TSCA Inventory or are exempt from the listing requirements.

SARA Title III Hazard Classes:

Fire Hazard - NO
 Reactive Hazard - NO
 Release of Pressure - NO
 Acute Health Hazard - NO
 Chronic Health Hazard - NO

STATE REGULATIONS:

This product contains the following components that are regulated under California Proposition 65:

Ingredient Name	Cancer	Reprod.	No Sign. Risk Lvl (ug/day)	
	List	List	California	Solvay
DIOXANE	Y	N	30	ND
ETHYLENE OXIDE	Y	Y	2	ND
ETHYL ACRYLATE	Y	N	ND	ND

16. OTHER INFORMATION

National Fire Protection Association Hazard Ratings--NFPA(R):

1 Health Hazard Rating--Slight
 1 Flammability Rating--Slight
 0 Instability Rating--Minimal

National Paint & Coating Hazardous Materials Identification System--HMIS(R):

1 Health Hazard Rating--Slight
 1 Flammability Rating--Slight
 0 Reactivity Rating--Minimal

Reason for Revisions:

Change of company name.

Key Legend Information:

ACGIH - American Conference of Governmental Industrial Hygienists
 OSHA - Occupational Safety and Health Administration
 TLV - Threshold Limit Value
 PEL - Permissible Exposure Limit
 TWA - Time Weighted Average
 STEL - Short Term Exposure Limit
 NTP - National Toxicology Program
 IARC - International Agency for Research on Cancer
 ND - Not determined

SOLVAY - Solvay Established Exposure Limits

Disclaimer:

The information herein is given in good faith but no warranty, expressed or implied, is made.

****End Of MSDS Document****